

HERITAGE TERRA COTTA BRICK REPAIR MORTAR (TB15)

Material Safety Data Sheet

COMPANY ID: U.S. Heritage Group, 3516 North Kostner Ave. Chicago, IL 60641

Date Issued: January 24, 2005 **Emergency Contact:** 773-286-2100

SECTION I: PRODUCT GROUP

PRODUCT GROUP:	Mortar for Terra Cotta & Brick	
PRODUCTS:	FORMULA:	CAS #:
Heritage Terra Cotta & Brick Repair Mortar (HS60)	NA	NA

SECTION II: INGREDIENTS

MATERIALS:	No known hazardous ingredients	

SECTION III: PHYSICAL DATA

Boiling Point:	NA
Specific Gravity:	2.5
Solubility in Water	11.2g/100g @ 18degrees C
Appearance and Odor:	Solid, white to light gray powder with low odor
рН	NA

SECTION IV: FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used):	None
Extinguishing Media:	Not Combustible
Special Fire Fighting Procedures:	Fire fighters should avoid all contact with this material. Self-contained breathing apparatus approved by NIOSH should be used if this material is present.
Unusual Fire & Explosion Hazards:	Product will not burn.

SECTION V: HEALTH HAZARD DATA EFFECTS OF OVEREXPOSURE

Acute:	Acute: May cause chronic irritation of nose, nasal ulcers, bronchitis or other lung
	problems. May cause skin rash, dermatitis. May cause eye irritation, conjunctivitis. When
	mixed with water as in mortar, may cause alkali burns if it comes in contact with skin or
	eyes.

US Heritage Group





HERITAGE TERRA COTTA BRICK REPAIR MORTAR (TB15)

Material Safety Data Sheet

	Eyes: Reduced visibility, may cause unpleasant deposits in eyes.		
	Skin: Contact causes irritation and may cause burns to the skin.		
	Inhalation: Irrit of the upper res	•	ory tract and can be damaging to the mucus membrane
	Ingestion: May	be corrosive to t	the digestive tract.
	Chronic: No chr	onic effects kno	wn
Emergency & First Aid Procedures:	Eyes: Flush eyes with water for 15 minutes, including upper lids. Call PHYSICIAN immediately.		
			with large amounts of water. Remove contaminated s, contact PHYSICIAN.
	Inhalation: Rem	nove to fresh air.	Contact PHYSICIAN immediately.
	_		sses of milk or water to drink, followed by fruit juices or alkali, consult a PHYSICIAN.
Carcinogenicity of Ingredients:	IARC	NTP	OSHA
	Not listed	Not listed	Not listed
Target Organ:	Lungs		
Medical Condition Which May Be Aggravated:	Pre-existing upp emphysema, ar	•	nd lung disease such as, but not limited to, bronchitis,
Primary Route of Entry:	Inhalation		

SECTION VI: REACTIVITY DATA

SECTION VI. REACTIVITY DATA	
Stability:	Stable
Conditions to Avoid:	Contact with boric oxide, acids, fluorine, and many organic materials.
Incompatibility:	Boric oxide, acids, fluorine, and many organic materials.
Hazardous Decomposition Products:	None
Hazardous Polymerization:	Will not occur

SECTION VII: SPILL OR LEAK PROCEDURES

Steps to be Taken in CaseThose involved in clean up must use personal protection against skin contact with mortar

US Heritage Group ner Ave., Chicago, IL 60641



info@usheritage.com or visit www.usheritage.com



HERITAGE TERRA COTTA BRICK REPAIR MORTAR (TB15)

Material Safety Data Sheet

Material Is Released or Spilled:	and inhalation of dust or mist (See section VIII). Keep spilled material away from acids. Carefully pick up the solid with a minimum of dusting and collect in metal containers with covers for disposal. The trace amounts of residue in the spill area can be flushed to the drain using plenty of water.
Waste Disposal Method	Add to water, dilute, and flush to the sewer. (Large amounts may require neutralization by acid.) Follow Federal, State and local regulation.

SECTION VIII: SPECIAL PROTECTION INFORMATION

Respiratory Protection:	Provide general ventilation and local exhaust ventilation to meet TLV requirements for lime dust. When dusty condition exists, a NIOSH approved dust respirator may also be needed. In the absence of dust or mist, mechanical exhaust is sufficient.
Protective Equipment:	Wear clean dry rubber gloves, clean body-covering protective clothing and approved eye protection selected for the conditions. An eye wash station and safety shower should be available.

SECTION IX: SPECIAL PRECAUTIONS

Precautions to be Taken In	Store material in sealed containers in a dry place, away from acids. Protect containers
Handling and Storage:	against physical damage.