

Safety and Datasheet (Complies with OSHA 29 CFR 1910.1200)

SECTION I: PRODUCT IDENTIFICATION

US Heritage Group 2900 N. Kearsarge Ave. Chicago, IL 60641

Revision: February 26, 2016

Product Name: NHL 2.0 Mortar NHL 2.0 Plaster NHL 3.5 Mortar NHL 3.5 Plaster NHL 5.0 Mortar NHL 5.0 Plaster

Product Code: HMB, HSB

Emergency Telephone Number (773)-286-2100

Information Telephone Number (773)-286-2100

WHMIS—Classification D2A: Materials Causing Other Toxic Effects E: Corrosive Material





Product Use: Hydraulic Lime repair mortar and plaster

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Hazardous Components CAS I	No. %		PEL (OSHA)	TLV (ACGIH)
			mg/M³	mg/M^3
Lime (Chemical), Hydraulic	85117-09-5	25-50	5	5
Silica Sand, crystalline	14808-60-7	50-75	10	0.025
			%SiO2+2	(respirable)

Other Limits: National Institute for Occupational Safety and Health (NIOSH). Recommended standard maximum permissible concentration=0.05 mg/M3 (respirable free silica) as determined by a full-shift sample up to 10-hour working day, 40-hour work week. See NIOSH Criteria for a Recommended Standard Occupational Exposure to Crystalline Silica.

US Heritage Group

2900 North Kearsarge Ave, Chicago IL 60641

P: 773.286.2100 F: 773.286.1852 E: info@usheritage.com



Safety and Datasheet (Complies with OSHA 29 CFR 1910.1200)

SECTION III - HAZARD IDENTIFICATION

Route(s) of Entry: Skin contact, Skin Absorption, Eye Contact, Inhalation, Ingestion

Acute Exposure:

Skin Severe irritation of mucous and skin, removes natural skin oils.

Eyes Severe eye irritation, intense watering of the eyes, possible lesions, possible blindness

when exposed for prolonged period.

Inhalation If inhaled in form of dust, irritation of breathing passages, coughing, sneezing.

Ingestion If ingested: pain, vomiting blood, diarrhea, collapse, drop in blood pressure (indicates

perforation of esophagus or stomach).

Chronic Exposure: Contact Dermatitis. Following repeated or prolonged contact, this product can cause redness, desquamation and fissures. This product may contain trace amounts of crystalline silica.

SECTION IV - First Aid Measures

Skin: Wash skin with cool water and pH-neutral soap or a mild detergent. Seek medical treatment if irritation or inflammation develops or persists. Seek immediate medical treatment in the event of burns.

Eyes: Immediately flush eye thoroughly with water. Continue flushing eye for at least 15 minutes, including under lids, to remove all particles. Call physician immediately.

Inhalation: Remove person to fresh air. If breathing is difficult, administer oxygen. If not breathing, give artificial respiration. Seek medical help if coughing and other symptoms do not subside. Inhalations of large amounts of Hemcrete Binder require immediate medical attention.

Ingestion: Do not induce vomiting. If conscious, have the victim drink water followed by diluted vinegar (1 part vinegar, 2 parts water) or fruit juice to neutralize the alkali. Call physician immediately.

General Advice: Contact a physician for all exposure except minor instances of skin contact.

SECTION V - FIRE AND EXPLOSION HAZARD DATA

Flammability: Noncombustible and not explosive. **Auto-ignition Temperature**: Not Applicable

Flash Points: Not Applicable

SECTION VI – ACCIDENTAL RELEASE MEASURES

If spilled, use dustless methods (vacuum) and place into covered container for disposal (if not contaminated or wet). Use adequate ventilation to keep exposure to airborne contaminants below the exposure limit.

US Heritage Group

2900 North Kearsarge Ave, Chicago IL 60641

P: 773.286.2100 F: 773.286.1852 E: info@usheritage.com



Safety and Datasheet (Complies with OSHA 29 CFR 1910.1200)

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND STORAGE

Do not allow water to contact the product until time of use. DO NOT BREATHE DUST. In dusty environments, the use of an OSHA, MSHA or NIOSH approved respirator and tight fitting goggles is recommended.

SECTION VIII – EXPOSURE CONTROL MEASURES

Engineering Controls: Local exhaust can be used, if necessary, to control airborne dust levels.

Personal Protection: The use of barrier creams or impervious gloves, boots and clothing to protect the skin from contact is recommended. Following work, workers should shower with soap and water. Precautions must be observed because burns occur with little warning -- little heat is sensed.

WARN EMPLOYEES AND/OR CUSTOMERS OF THE HAZARDS AND REQUIRED OSHA

PRECAUTIONS ASSOCIATED WITH THE USE OF THIS PRODUCT. **Exposure Limits**: Consult local authorities for acceptable exposure limits

SECTION IX - PHYSICAL/CHEMICAL CHARACTERISTICS

Appearance: Fine gray powder with no distinct odor.

Specific Gravity: Not Available

Boiling Point: 212° F

Vapor Density: Not Available

Solubility in Water: Slight

pH: 10.5

Melting Point: Not Available Vapor Pressure: Not Available Evaporation Rate: Not Available

Odor: Not Available

Volatile Organic Content (VOC): 0 g/L

SECTION X - REACTIVITY DATA

Stability: Stable.

Incompatibility (Materials to Avoid): Contact with boric oxide, acids, fluorine, and many organic materials. Hazardous Decomposition or By-products: Boric oxide, acids, fluorine, and many organic materials.

Hazardous Polymerization: Will Not Occur.

Condition to Avoid: Keep sealed until used to preserve product utility.

SECTION XI – TOXICOLOGICAL INFORMATION

Routes of Entry: Skin Contact, Eye Contact, Ingestion

Toxicity to Animals:

LD50: Not Available LC50: Not Available

US Heritage Group

2900 North Kearsarge Ave, Chicago IL 60641

P: 773.286.2100 F: 773.286.1852 E: info@usheritage.com



Safety and Datasheet (Complies with OSHA 29 CFR 1910.1200)

Chronic Effects on Humans: Conditions aggravated by exposure include eye disease, skin disorders and

Chronic Respiratory conditions.

Special Remarks on Toxicity: Not Available

SECTION XII - ECOLOGICAL INFORMATION

Ecotoxicity: Not Available BOD5 and COD: Not Available

Products of Biodegradation: Not available

Toxicity of the Products of Biodegradation: Not available

Special Remarks on the Products of Biodegradation: Not available

SECTION XIII – DISPOSAL CONSIDERATIONS

Waste Disposal Method: Add to water, dilute, and flush to the sewer. (Large amounts may require neutralization by acid.) Follow Federal, State and local regulation. Alternately, waste lime can be used for neutralizing plant acid wastes.

SECTION XIV - TRANSPORT INFORMATION

Not hazardous under U.S. DOT and TDG regulations.

SECTION XV - OTHER REGULATORY INFORMATION

US OSHA 29CFR 1910.1200: Considered hazardous under this regulation and should be included in the employers' hazard communication program

SARA (Title III) Sections 311 & 312: Qualifies as a hazardous substance with delayed health effects

SARA (Title III) Section 313: Not subject to reporting requirements

TSCA (May 1997): Some substances are on the TSCA inventory list

Federal Hazardous Substances Act: Is a hazardous substance subject to statues promulgated under the subject act

California Regulation: WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

Canadian Environmental Protection Act: Not listed

Canadian WHMIS Classification: Considered to be a hazardous material under the Hazardous Products Act as defined by the Controlled Products Regulations (Class D2A, E- Corrosive Material) and subject to the requirements of Health Canada's Workplace Hazardous Material Information (WHMIS). This product has

US Heritage Group

2900 North Kearsarge Ave, Chicago IL 60641

P: 773.286.2100 F: 773.286.1852 E: info@usheritage.com



Safety and Datasheet (Complies with OSHA 29 CFR 1910.1200)

been classified according to the hazard criteria of the Controlled Products Regulation (CPR). This document complies with the WHMIS requirements of the Hazardous Products Act (HPA) and the CPR.

SECTION XVI - OTHER INFORMATION

HMIS: Dispersed Hydrated Lime

3 HEALTH
0 FLAMMABILITY
1 REACTIVITY

DZA,

Materials Causing Other Toxic EffectsCorrosive Materials

PERSONAL PROTECTION

NFPA:



WHMIS—Classification:

WHMIS—Classification:

"E" Corrosive Materials

"D2A" Materials Causing Other Toxic Effects

Symbol:



Symbol:



Abbreviations:

ACGIH American Conference of Government Industrial Hygienists

CAS Chemical Abstract Service

CERCLA Comprehensive Environmental Response, Compensation and Liability Act

CFR Code of Federal Regulations

CPR Controlled Products Regulations (Canada)

DOT Department of Transportation
IARC International Agency for Research
MSHA Mine Safety and Health Administration

NIOSH National Institute for Occupational Safety and Health

NTP National Toxicity Program

OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit

US Heritage Group

2900 North Kearsarge Ave, Chicago IL 60641

P: 773.286.2100 F: 773.286.1852 E: info@usheritage.com



Safety and Datasheet (Complies with OSHA 29 CFR 1910.1200)

RCRA Resource Conservation and Recovery Act

SARA Superfund Amendments and Reauthorization Act

TLV Threshold Limit Value
TWA Time-weighted Average

WHMIS Workplace Hazardous Material Information System

Last Updated: February 26, 2016

NOTE: The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to silica contained in our products. END OF MSDS.